

Product Codes:  
Timer-77-1/2"

# DIGITAL 7-DAY ON/OFF WATER CONTROL

## TIMER-77

## Product Specification

The **digital seven-day timed water on/off control** can be set to switch the **water** on at the **start** of the **working day** and the **water off** when the building is no longer in use, **preventing** potential **water loss** due to **leaking** fittings or **vandalism**. Ideal for use in situations which follow regular routines such as site services, manufacturing, education, commercial spaces, healthcare and other services. The water timer can be programmed for daily, weekly, weekday/weekend operation and has a manual override function to cover many situations.

Making **installation quick** and **easy** the timer is **pre-wired** ready for use and is **supplied** complete **with** a **½"** **brass WRAS approved solenoid valve** for immediate use. The fitter simply connects the timer to a **230 VAC** supply from a spur outlet or using a 13 amp plug.



## Product Features      Technical Specifications

- Simple to programme
- 24-hour digital LCD display
- Automatic summer/winter changeover
- Shortest switching time 1 minute
- Pre-wired easy to install, ideal for wall mounting
- On/off switch and manual override
- Power and output status LEDs
- Complete with ½" fail safe Normally Closed **WRAS** approved valve

|                       |                                                                                                                                                                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Programming options   | Up to four on and off programmes per day, including: <ul style="list-style-type: none"> <li>• 7 days the same (24 hours)</li> <li>• 5 &amp; 2 days (where weekdays &amp; weekend days are the same)</li> <li>• 7 individual days</li> </ul> |
| Solenoid valve        | Brass Normally Closed (fail safe), 1/2" British Standard Pipe (BSP) female threads, 13.5 mm orifice, pressure range 0.35 – 10 bar, WRAS approved                                                                                            |
| Power supply          | 230 V, 50 Hz                                                                                                                                                                                                                                |
| Contact type          | Normally Open, maximum load 13 amp resistive, 5 amp inductive                                                                                                                                                                               |
| Cables                | Power and valve cables are supplied to a nominal 2 m length. Core size is 0.75 mm²                                                                                                                                                          |
| Enclosure             | Size 88 x 88 x 60 mm (exc. cable glands) in white PVC suitable for wall mounting                                                                                                                                                            |
| Operating temperature | 0° to 40°C                                                                                                                                                                                                                                  |



Saving more than water

[watersavers.co.uk](http://watersavers.co.uk) | T 01603 720999 | E [info@watersavers.co.uk](mailto:info@watersavers.co.uk)

**Watersavers Ltd**  
**Church Field Road**  
**Chilton Industrial Estate**  
**Sudbury**  
**Suffolk CO10 2YA**

Designed & Manufactured  
in the UK

